

Robotic High Pressure Arch




Available in 2 -3 or 5 Water Spray
Manifold Configurations



Oscillating Follower
Top Blaster Manifold



Oscillating Follower Horizontal
Wheel Blaster Manifold



Oscillating Follower Vertical
Side Blaster Manifold

DIMENSIONS:

- Equipment Height – 124"
- Vehicle Height Clearance – 101"
- Tunnel Length – 36"

SPECIFICATIONS:

- Free standing
- Arch is constructed of 4" x 4" - #304 stainless steel
- Option of Three, Four, or Water Five spray manifolds
- Requires 15 HP Water pump
Standard - Hydra-cell (Wanner) for (Recycled Water)
Optional - General pump or Cat pump
For (Fresh water only)
- Optional 2 x 15Hp pressure unit available
- 2 HP Hydraulic power pack required for oscillation

PERFORMANCE

- Automatically tracks the vehicle's Front & Rear bumpers, top and sides.
- Independent hydraulic motors used to oscillate the water spray manifolds
- Heavy-duty air-cylinders positions the water spray manifolds
- Stainless steel water manifold with 12 brass nozzles per each spray bar
- No grease UHMW self-lubricating bushings
- No electric eyes
- Available in a variety of water spray combinations

www.washngo.com

Vehicle Wash Systems, Inc. 63 Winter Street
P.O. Box 414 Weymouth, MA 02188 • 800 -344-8700 • Fax: 781-331-8701

WASH-N-GO
Car Wash Professionals